

THUILE
PORCELAIN TILE



WEBSITE

WHITE




TECHNICAL INFORMATION	
SHADE VARIATION:	V2
RELIEF:	NO
GRAPHIC DEVELOPMENT:	
120X120 47"X47" RECT	7 FACES
60X120 24"X47" RECT	11 FACES

374
—
375

Wall | Thuile White PUL Rect. 60X120cm · 24"X47"
Floor | Thuile White PUL Rect. 120X120cm · 47"X47"

PORCELAIN TILE RECT.
POLISHED



COLOR	120X120CM · 47"X47"	60X120CM · 24"X47"
WHITE	CAR7CS	CASICS

THUILE
PORCELAIN TILE



WEBSITE

VENATO NATURAL



TECHNICAL INFORMATION	
SHADE VARIATION:	V3
SLIP RESISTANCE:	
MATT	C1/ R9A
RELIEF:	NO
GRAPHIC DEVELOPMENT:	
60X120 24"X47" RECT	11 FACES

376
—
377



Floor | Thuille Venato Natural MT Rect. 60X120cm · 24"X47"

PORCELAIN TILE RECT
MATT



COLOR	60X120CM · 24X47"
VENATO NATURAL	CANSES

THUILE
PORCELAIN CLAY TILE



WEBSITE

WHITE



TECHNICAL INFORMATION	
SHADE VARIATION:	V2
RELIEF:	NO
GRAPHIC DEVELOPMENT:	
120X120 47"X47" RECT	7 FACES
60X120 24"X47" RECT	11 FACES

378
—
379



Wall | Thuille White SAT Rect. 60X120cm · 24"X47"
Floor | Thuille White SAT Rect. 120X120cm · 47"X47"







PORCELAIN CLAY TILE RECT.
SAT



COLOR	120X120CM · 47"X47"	60X120CM · 24"X47"
WHITE	CAR3ES	CAN5ES

UNE-14411

CLASIFICACIÓN NORMALIZADA SEGÚN · STANDARD CLASSIFICATION ACCORDING TO

ENSAYOS	NORMA	GRUPO BIa Pavimento Porcelánico Esmaltado Glazed porcelain tiles	GRUPO BIb Pavimento Gres Espesorado y Porcelánico AB Glazed thick floor tiles and Porcelain AB	GRUPO BIIa Pavimento Gres Gres floor tiles	GRUPO BIII Revestimiento Wall tiles	
 Absorción de agua Water absorption	UNE-EN-ISO 10545-3	Ev ≤ 0,5%	0,5% < Ev ≤ 3%	3% < Ev ≤ 6%	Ev > 10%	
 Fuerza de rotura Breaking strength	UNE-EN-ISO 10545-4	≥ 1300 N	≥ 1100 N	≥ 1000 N	≥ 600 N	
 Resistencia a la flexión Modulus of rupture	UNE-EN-ISO 10545-4	≥ 35 N/mm ²	≥ 30 N/mm ²	≥ 22 N/mm ²	≥ 12 N/mm ²	
 Abrasión superficial Surface abrasion	UNE-EN-ISO 10545-7	Consultar ficha técnica Consult technical sheet	Consultar ficha técnica Consult technical sheet	Consultar ficha técnica Consult technical sheet	-	
 Resistencia al cuarteo Crazing resistance	UNE-EN-ISO 10545-11	Requerido Requested	Requerido Requested	Requerido Requested	Requerido Requested	
 Resistencia a la helada Frost resistance	UNE-EN-ISO 10545-12	Requerido Requested	Requerido Requested	-	-	
 Resistencia química / Chemical resistance	Productos domésticos y de piscina Household chemicals and swimming pools salts	UNE-EN-ISO 10545-13	Mínimo clase B Minimum class B	Mínimo clase B Minimum class B	Mínimo clase B Minimum class B	Mínimo clase B Minimum class B
	Ácidos a baja concentración Low concentration of acids	UNE-EN-ISO 10545-13	Mínimo clase LB Minimum class LB	Mínimo clase LB Minimum class LB	Mínimo clase LB Minimum class LB	Mínimo clase LB Minimum class LB
	Bases a baja concentración Low concentration of alkalis	UNE-EN-ISO 10545-13	Mínimo clase LB Minimum class LB	Mínimo clase LB Minimum class B	Mínimo clase LB Minimum class B	Mínimo clase LB Minimum class B
 Resistencia a las manchas Resistance to stains	UNE-EN-ISO 10545-14	Mínimo clase 3 Minimum class 3	Mínimo clase 3 Minimum class 3	Mínimo clase 3 Minimum class 3	Mínimo clase 3 Minimum class 3	

